



General Purpose Glass Cloth Tape

3615

Technical Data

March, 2014

Product Description

3M™ Glass Cloth Tape 3615 is a general purpose, easy unwind tape coated with a silicone adhesive for many applications requiring high-temperature resistance, high adhesion, and a very strong, abrasion-resistant backing.

Product Construction

Backing	Adhesive	Color	Standard Roll Size
Glass cloth	Silicone	White	36 yds. (33 m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	35 oz./in. width (38 N/100 mm)	D-3330
Tensile Strength:	180 lbs./in. width (3140 N/100 mm)	D-3759
Elongation:	7%	D-3759
Backing Thickness:	5.0 mils (.13 mm)	D-3652
Total Tape Thickness:	7.0 mils (.18 mm)	D-3652

Features

- Can be used from -65 to 450°F (-54 to 232°C) or greater.
- Can withstand intermittent temperatures up to 550°F (288°C) or higher, depending upon the type and duration of the heat source.
- Glass cloth for high tensile strength to provide a permanent seal.
- Silicone adhesive for long aging, good holding power for a wide operating range to help increase productivity.

Application Ideas

- High temperature applications requiring high tensile strength and good holding power.
- Easy unwind for ease of application.
- Permanent sealing of high temperature ducts or chambers.
- As back up strip for submerged arc welding.

3M™ General Purpose Glass Cloth Tape

3615

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 50% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within 24 months from date of manufacture.

Technical Information The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.

If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/iatd



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2014 (3/14)