classiX° all-steel bar clamps

Bar clamps for industrial application



An opening price point offering that embodies the stringent quality requirements of BESSEY®.

Features & Benefits

Choices

The classiX® line is an abbreviated range of the most popular global clamp performance characteristics. A variety of throat depths, pad/swivel styles and clamping capacities provide professionals with a choice that makes sense for real-world applications.

Quality

Internationally sourced components coordinated by BESSEY® quality control and engineering departments ensure great prices and great quality.

Standard pads and heavy duty pads

The standard swivel pads and heavy duty pads are tried and true contact surfaces for use with your classiX clamps. Field replaceable.

Hardened spindle

Heat-treated, high carbon Acme threaded spindle is manufactured to offer high load capacity, durability and spatter resistance.



	01 .	T 1 (
	Clamping Capacity	Throat Depth	Clamping Force	Approx. Weight
classiX° - Standard pad				
GS12-8K	4"	3 1/ 8"	550 lbs.	0.5 lbs.
GS16K	6"	3 1/8"	550 lbs.	0.6 lbs.
GS20K	8"	4"	880 lbs.	1.8 lbs.
GS16-12K	6"	4 3/4"	1000 lbs.	2.0 lbs.
GS25K	10"	4 3/4"	1000 lbs.	2.5 lbs.
GS30K	12"	5 ¹ / ₂ "	1200 lbs.	4.3 lbs.
GS60K	24"	4 3/4"	1200 lbs.	5.1 lbs.
classiX® - Heavy duty pad				
GSL30	12"	4 3/4"	1880 lbs.	5.0 lbs.
GSL60	24"	4 3/4"	1880 lbs.	6.5 lbs.
GSM20	7 1/2"	4 3/4"	2660 lbs.	5.2 lbs.
GSM25	9"	5 ¹ /2"	2660 lbs.	6.0 lbs.
GSM30	12"	5 ¹ /2"	2660 lbs.	7.0 lbs.
GSM40	16"	5 ¹ / ₂ "	2660 lbs.	7.5 lbs.
GSM50	20"	5 ¹ / ₂ "	2660 lbs.	7.7 lbs.
GSM60	24"	5 ¹ / ₂ "	2660 lbs.	8.0 lbs.
classiX® - Lever bar clamp				
GSH12	4"	2 %"	400 lbs	1.10 lbs
GSH20	8"	4"	600 lbs	2.50 lbs
GSH30	12"	5 ½"	1110 lbs	5.00 lbs
GSH50	20"	4 3/4"	1110 lbs	6.25 lbs

classiX® GSH all-steel lever bar clamps

- Quick up to 5 times faster than regular clamps!
- Secure, unaffected by vibrations.
- Strong high clamping force up to 1110 lbs.
- Non-slip trigger release.

















Rev. Jun/14