


DUPONT™ TYCHEM® 4000 SL120B WH

GARMENT TECHNICAL DATA SHEET



This picture is for measurement reference only.

Customer Service:

United States 1-800-931-3456

Canada 1-800-387-9326

SafeSpec Home Page

Seams and closures have less barrier than fabric. Note: for protection from hazardous or infectious liquids, additional barrier tests are required to establish suitability for use. CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under the specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and obsures may provide less barrier than the fabric. It the fabric becomes form, abraded, or punctured, end-user should discontinue use of garment to avoid compromising the barrier protection. SINGE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION ON WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY OF THIS INFORMATION. This information is not intended as a license to others covering any material or its use. Data presented does not comprise a product specification.

Warning: Cleanroom apparel should not be used around heat, flames, sparks or in potentially flammable or explosive environments. Cleanroom fabrics should have slip-resistant materials on the outer sole of boots, shoe covers, or other garment surfaces in conditions where slipping could occur.

Silicone Statement: In the past, DuPont has found that threads and zippers can be the most significant source of silicone oil contamination in garments. DuPont specifies that thread and zippers used in DuPont[™] Tyvek® IsoClean® and ProClean® garments be manufactured without the use of silicone oils. For end uses with concerns about contamination with silicone oils or any other contaminants, the best practice is to audit inbound materials, including garments, for those contaminants.

Latex Statement: As of January 1, 2006, DuPont production specifications exclude use of components containing natural rubber latex in the manufacture of DuPont** Tyvek® IsoClean® and ProClean® garments. Anyone who begins to exhibit allergic response during the use of DuPont products should immediately cease using these products. The incident should also be reported to DuPont at 1,800.441.3637.

Measurements are approximate values intended to assist in proper size selection. Normal variability may result in slight differences in actual garment sizes.

Copyright @ 2013 DuPont. All rights reserved. The DuPont Oval Logo, DuPontTM, The miracles of science TM , and all products denoted with @ or TM are trademarks or registered trademarks of E.i. du Pont de Nemours and Company or its affiliates. Printed on . November 28, 2018

PRODUCT INFORMATION

ATTRIBUTES

DuPont™ Tychem® 4000 Coverall. Collar. Open Wrists and Ankles. Storm Flap with

Adhesive Closure. Bound Seams. White

SL120BWHxx0012yy (xx=size;yy=option code)

CATALOG NUMBER

When ordering, replace xx with desired size.

FABRIC	DESIGN	SEAM	COLOR	CASE COUNT	SIZES	OPTION CODES
Tychem® 4000	Coverall w/ Open Wrists and Ankles	Bound	White	12 per case	MD, LG, XL, 2X, 3X, 4X, 5X, 6X	00

TYPICAL FINISHED DIMENSIONS

OPTION CODE	DESCRIPTION	SIZES	PART NUMBER
00	Standard	MD, LG, XL, 2X, 3X, 4X, 5X, 6X	SL120BWHxx001200

PHYSICAL PROPERTIES -	Typical values, not specifications.	
PROPERTY	TEST METHOD	RESULT
Thickness	ASTM D1777	12 mils
Basis Weight	ASTM D3776	3.6 oz/yd ²
Burst Strength - Mullen	ASTM D3786	73 psi
Breaking Strength - Grab (MD)	ASTM D5034	44 lb _f
Breaking Strength - Grab (CD)	ASTM D5034	52 lb _f
Wearing Apparel Flammability	16 CFR 1610 🕙	Class 1