



PRODUCT DATA SHEET

Synthetic Brake & Caliper Grease, 12 Wt Oz
 No. SL3303 | Item# 1007902 | Case# 1007901



Product Description	A specially developed synthetic grease with a high-tech formula for use in disc & drum brake systems. High temperature grease is plastic & rubber safe. Use on metal to metal contact points and sliding surfaces. Resists moisture and will not washout.
Applications	Backing plates, brake pad contact points, caliper o-rings, calipers, disc brake pads, drum brake systems, grommets, parking brake areas of lubrication, pivot points, self adjusters
Unit Package Description	12 Ounce Tub With Brush
Brand	Sta-Lube
Generic Description 1	Brake Caliper Synthetic Grease
Net Fill	12 Wt Oz
UPC Code	072213330304
Unit Dimensions	4.25H x 4W x 4D in
Units Per Case	12
Case Dimensions	5H x 12.25W x 16D in
Cases Per Pallet	64
Case Weight	11 lbs
I 2 of 5 Code	30072213330305
Appearance	Black Semi-Solid Grease
Base Type	Synthetic base with Molybdenum Disulfide, PTFE and Graphite
Flash point (F)	450°F
Flash point (C)	232°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.89
NLGI Grade	2
Timken OK Load Lbs.	60 Lbs
Plastic Safe	Yes
Evaporation Rate	Slow

Last revised: 11/30/2017
 Page 1 of 2



Customer Care: 800-556-5074
 Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Working Temp (F)	-30 to 600°F
Working Temp (C)	-45.5 to 232°C
4 Ball EP	Not Determined
4 Ball Wear	0.67 mm
Drop Point	None
Leakage	None
Oil Separation	Not Determined
Oxidation Stability	5
Pour Point (F)	-20°F
Pour Point (C)	-29°C
ISO Viscosity Grade	Not Determined
Water Washout	1.7
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0.58
VOC g/L (Consumer Product def)	5.62
VOC lbs/gal (Consumer Prod def)	0.04
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 11/30/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.