

SPECIFICATION SHEET STYLE: 250-96-0520



Technical Data

Sizes AvailableOSPackagingBagged EachPacked144 Pair/CaseCase Dimensions (cm)54.60 x 30.50 x 40.00Case Weight (kg)Country of OriginTaiwanLensClearFrame StyleOver-The-GlassLens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectricCertificationsANSI Z87.1+, TAA Compliant	Color	Clear
Packed144 Pair/CaseCase Dimensions (cm)54.60 x 30.50 x 40.00Case Weight (kg)Country of OriginTaiwanLensClearFrame StyleOver-The-GlassLens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Sizes Available	OS
Case Dimensions (cm)54.60 x 30.50 x 40.00Case Weight (kg)Country of OriginTaiwanLensClearFrame StyleOver-The-GlassLens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Packaging	Bagged Each
Case Weight (kg)Country of OriginTaiwanLensClearFrame StyleOver-The-GlassLens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Packed	144 Pair/Case
Country of OriginTaiwanLensClearFrame StyleOver-The-GlassLens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Case Dimensions (cm)	54.60 x 30.50 x 40.00
LensClearFrame StyleOver-The-GlassLens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Case Weight (kg)	
Frame StyleOver-The-GlassLens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Country of Origin	Taiwan
Lens ColorClearFrame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Lens	Clear
Frame FitUniversalLens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Frame Style	Over-The-Glass
Lens CoatingFogLess 3SixtyBridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Lens Color	Clear
BridgeMoldedTempleMoldedDiopterBase CurveConstructionDielectric	Frame Fit	Universal
TempleMoldedDiopterBase CurveConstructionDielectric	Lens Coating	FogLess 3Sixty
Diopter Base Curve Construction Dielectric	Bridge	Molded
Base Curve Construction Dielectric	Temple	Molded
Construction Dielectric	Diopter	
	Base Curve	
Certifications ANSI Z87.1+, TAA Compliant	Construction	Dielectric
	Certifications	ANSI Z87.1+, TAA Compliant

OverSeal™

OTG Safety Glasses with Headband, Clear Lens, Fogless® 3Sixty™ Coating

• Over-the-glass design helps keep prescription eyewear users in compliance

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU® AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2022-03-01